

Mounted Unit

BEARING DIMENSIONS

Shaft Diameter	Complete* Component	Pedestal Housing	A**	B	C‡	D	E		F	H	Bolts	Weight lbs.
							Minimum	Maximum				
2 11/16 2 3/4 2 15/16 3 70 mm 75 mm	S2 SAFH 211 S2 SAFH 212 S2 SAFH 215 S2 SAFH 300 S2 SAFH 70mm S2 SAFH 75mm	SAF517	3 3/4	13	3 1/2	1 1/16	9 7/8	11	2 1/8	9 3/8	Four 5/8	56
3 3/16 3 1/4 3 7/16 3 1/2 80 mm 85 mm 90 mm	S2 SAFH 303 S2 SAFH 304 S2 SAFH 307 S2 SAFH 308 S2 SAFH 80mm S2 SAFH 85mm S2 SAFH 90mm	SAF520	4 1/2	15 1/4	4 3/8	1 3/4	11 5/8	13 1/8	2 3/8	10 5/16	Four 3/4	75
3 11/16 3 3/4 3 15/16 4 100 mm 105 mm	S2 SAFH 311 S2 SAFH 312 S2 SAFH 315 S2 SAFH 400 S2 SAFH 100mm S2 SAFH 105mm	SAF522	4 15/16	16 1/2	4 3/4	2	12 5/8	14 1/2	2 3/4	11 11/16	Four 3/4	120
4 3/16 4 1/4 4 7/16 4 1/2 110 mm 115 mm	S2 SAFH 403 S2 SAFH 404 S2 SAFH 407 S2 SAFH 408 S2 SAFH 110mm S2 SAFH 115mm	SAF526	6	18 3/8	5 1/8	2 3/8	14 5/8	16	3 1/4	13 5/8	Four 7/8	180
4 11/16 4 15/16 5 120 mm 125 mm 130 mm	S2 SAFH 411 S2 SAFH 415 S2 SAFH 500 S2 SAFH 120mm S2 SAFH 125mm S2 SAFH 130mm	SAF528	6	20 1/8	5 7/8	2 3/8	16	17 1/8	3 3/8	14 5/8	Four 1	225
5 3/16 5 7/16 5 1/2 140 mm	S2 SAFH 503 S2 SAFH 507 S2 SAFH 508 S2 SAFH 140mm	SAF532	6 11/16	22	6 1/4	2 11/16	17 3/8	19 1/4	3 3/4	16 11/16	Four 1	290
5 15/16 6 150 mm 155 mm	S2 SAFH 515 S2 SAFH 600 S2 SAFH 150mm S2 SAFH 155mm	SAF534	7 1/16	24 3/4	6 3/4	2 3/16	19 3/8	21 5/8	4 1/4	16 13/16	Four 1	335

* Specify Suffix – FL for float bearing,
HD for held bearing
** Base to center height can be altered upon request

Special application bearings are available upon request.
‡ Housing width only

Dimensions in inches
Normal operating temperature for
standard bearings is 32°F to 212°F

